

Loyal IKO CRB14025 Cross Cylindrical Roller Bearing

Loyal IKO CRB14025 Cross Cylindrical Roller Bearing Industries and Applications ? 21 Outer Diameter (mm) We sell discount online 12x21x23 Size (mm) as well as cheap machinery parts.

Size (mm)	12x21x23
Bore Diameter (mm)	12
Outer Diameter (mm)	21
Width (mm)	23
Fw	12 mm
D	21 mm
C – 23 mm / Tolerance: -0,25	23 mm / Tolerance: 0,25
C1 – 9 mm / Tolerance: -0,2	9 mm / Tolerance: 0,2
C2	6,5 mm
D2 max	27,2 mm
da	21,7 mm
dw	12 mm / Tolerance: E8
ra max	0,3 mm
rmin	0,3 mm
m	40 g / Weight
Cr	10100 N / Dynamic load rating (radial)
C0r	11000 N / Static load rating (radial)
Ca	10300 N / Dynamic load rating (axial)

C0a	15400 N / Static load rating (axial)
Cur	1920 N / Fatigue limit load, radial
Cua	740 N / Fatigue limit load, axial
nG	11000 1/min / Limiting speed
Inventory	7.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.5
EAN	4012802702934
Product Group	B04144
Rolling Element	Combination – Needle Roller and Thrust Ball Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Other Features	With Grease Retaining Cap
Long Description	12MM Bore 1; 12MM Bore 2; 21MM Outside Diameter; 23MM Height; Combination – Needle Roller and Thrust
Inch – Metric	Metric
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.40
Noun	Bearing

Keyword String	Combination
Manufacturer Item Number	NKX12Z
Weight / LBS	0.084
Bore 1	0.472 Inch 12 Millimeter
Bore 2	0.472 Inch 12 Millimeter
Outside Diameter	0.827 Inch 21 Millimeter
Height	0.906 Inch 23 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter