

# Loyal Manipulator Bearing SX011820

What is Loyal Manipulator Bearing SX011820 in mechanical engineering? Manufacturing Service . Upload your CAD file 72 Outer Diameter (mm) for an instant. 35x72x17 Size (mm)

Size (mm)	35x72x17
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Width (mm)	17
d	35 mm
D	72 mm
B	17 mm
C	17 mm
r min.	1,1 mm
da min.	41,5 mm
da max	44,5 mm
Da max.	65,5 mm
ra max.	1 mm
Weight	0,284 Kg
Basic dynamic load rating (C)	25,7 kN
Basic static load rating (C0)	15,3 kN
(Grease) Lubrication Speed	6 300 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.288
EAN	0029176064326

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Rubber Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6207DDU
Weight / LBS	0.63492
Outside Diameter	2.835 Inch   72 Millimeter
Outer Race Width	0.669 Inch   17 Millimeter
Bore	1.378 Inch   35 Millimeter
Inner Race Width	0 Inch   0 Millimeter
SRI	5.61
hidYobi	6207DDU
LangID	1
D_	72

SREX	0.05
B_	17
da min	41.5
hidTable	ecat_NSRDGB
SRE	5.89
mass	0.284
GRS rpm	6300
ra	1
SRIX	0.025
D_a	65.5
SRIN	0
C0	15.3
fo	13.8
SREN	0
DE_	64.612
Prod_Type3	DGBB_SR_DD
DA_	11.112
bomp	0
Z_	9
yobi	6207DDU
C_conv	25700
ALPHA_	0
SDM_	53.5
r	1.1
KBRG	6161
SBRG	2
DI_	42.388