

Loyal Potshell carrier vehicle slewing ring XSA140544-N

Browse Loyal Potshell carrier vehicle slewing ring XSA140544-N 140x90x24 Size (mm) Categories in the 140 Bore Diameter (mm) Manufacturers Online Free. including .

| | |
|-------------------------------|-----------|
| Size (mm) | 140x90x24 |
| Bore Diameter (mm) | 140 |
| Outer Diameter (mm) | 90 |
| Width (mm) | 24 |
| d | 90 mm |
| D | 140 mm |
| B | 24 mm |
| D1 | 122.1 mm |
| F | 103 mm |
| r1,2 – min. | 1.5 mm |
| r3,4 – min. | 1.1 mm |
| s | 3.5 mm |
| da – min. | 96 mm |
| da – max. | 101 mm |
| db – min. | 106 mm |
| Da – max. | 133 mm |
| ra – max. | 1.5 mm |
| rb – max. | 1 mm |
| Basic dynamic load rating – C | 80.9 kN |
| Basic static load rating – C0 | 104 kN |

| | |
|-----------------------------|------------|
| Fatigue load limit – Pu | 12.7 kN |
| Reference speed | 5600 r/min |
| Limiting speed | 5600 r/min |
| Calculation factor – kr | 0.1 |
| D1 ≈ | 122.1 mm |
| r1,2 min. | 1.5 mm |
| r3,4 min. | 1.1 mm |
| s max. | 3.5 mm |
| da min. | 96 mm |
| da max. | 101 mm |
| db min. | 106 mm |
| Da max. | 133 mm |
| ra max. | 1.5 mm |
| rb max. | 1 mm |
| Basic dynamic load rating C | 80.9 kN |
| Basic static load rating C0 | 104 kN |
| Fatigue load limit Pu | 12.7 kN |
| Calculation factor kr | 0.1 |
| Limiting value e | 0.2 |
| Axial load factor Y | 0.6 |
| Mass bearing | 1.33 kg |