

# Loyal RKS.221310101001 Customized crossed cylindrical roller slewing bearing with an external gear

170 Million used Loyal RKS.221310101001 Customized crossed cylindrical roller slewing bearing with an external gear instantly searchable. Shop our large selection of parts based on brand, price, description, and 20 mm d location. Order the with stock ...

d	20 mm
D	42 mm
B	12 mm
d1	26.6 mm
d2	24.8 mm
D1	34.21 mm
K	0.5 mm
C1	3.67 mm
r1,2 min.	0.6 mm
r3,4 min.	0.3 mm
a	10.2 mm
da min.	22 mm
db min.	22 mm
Da max.	40 mm
Db max.	39.6 mm
ra max.	0.6 mm
rb max.	0.3 mm

dn	28.1 mm
Basic dynamic load rating C	7.41 kN
Basic static load rating C0	3.35 kN
Fatigue load limit Pu	0.143 kN
Attainable speed for grease lubrication	65000 r/min
Attainable speed for oil-air lubrication	100000 r/min
Ball diameter Dw	6.35 mm
Number of balls z	12
Reference grease quantity Gref	1.1 cm <sup>3</sup>
Preload class A GA	40 N
Static axial stiffness, preload class A	23 N/μm
Preload class B GB	120 N
Static axial stiffness, preload class B	36 N/μm
Preload class C GC	235 N
Static axial stiffness, preload class C	49 N/μm
Calculation factor f	1.04
Calculation factor f1	1
Calculation factor f2A	1
Calculation factor f2B	1.03
Calculation factor f2C	1.05
Calculation factor fHC	1.01
Calculation factor f0	7.2
Mass bearing	0.056 kg