

Loyal XR889058 Cross tapered roller bearing

Loyal XR889058 Cross tapered roller bearing manufacturer and global supplier of reliable ball and 289.999 mm Da roller ... Loyal XR889058 Cross tapered roller bearing Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of 173.037 mm da our targeted industries.

da	173.037 mm
Da	289.999 mm
Ca	89.789 mm
A1	158.75 mm
A2	225.425 mm
ba	69.85 mm
H	338.137 mm
H1	169.875 mm
H2	66.675 mm
L	558.8 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	47.625 mm
Housing	SSAFS 038 KA
Bearing	23038 CCK/W33
Adapter sleeve assembly	SNW 3038×6.13/16
Stabilizing ring	2 x 38151-38
Labyrinth ring	2 x LOR 153

PosiTrac Plus contact element	2 x B10724-155
End plug (suffix Y)	EPR 21
Max. speed for PosiTrac Plus seal	825 r/min
P60°	345 kN
P90°	207 kN
P120°	133 kN
P150°	120 kN
P180°	145 kN
Pa	42.9 kN
Mass pillow block	132 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	793.8 g