

LS GE260XT-2RS plain bearings

Manufacturers of all are represented 100 mm da 114.3 mm db in our partial list of clients. Contact Gary for a complete LS GE260XT-2RS plain bearings list of clients and projects.

da	100 mm
db	114.3 mm
dc	96.838 mm
Da	215.001 mm
Ca	82.804 mm
A1	120.65 mm
A2	187.325 mm
ba	45.244 mm
H	258.762 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	55.563 mm
Housing	SAF 320
Bearing	1320

Lock nut	AN 20
Lock washer	W 20
Stabilizing ring	2 x SR-1620
Labyrinth ring (db shaft position)	LOR 118
PosiTrac Plus contact element (db shaft position)	B10724-117
Labyrinth ring (dc shaft position)	LOR 106
PosiTrac Plus contact element (dc shaft position)	B10724-106
End plug (suffix Y)	EPR 12
Max. speed for PosiTrac Plus seal	1300 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	52.5 kN
Mass pillow block	44.5 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	765.45 g