

LS GEC320XF/Q plain bearings

Enjoy High Margins 110x170x60 Size (mm) on 110 Bore Diameter (mm) Competitive 170 Outer Diameter (mm) Pricing.Great Wholesale Products at Low Costs.

Size (mm)	110x170x60
Bore Diameter (mm)	110
Outer Diameter (mm)	170
Width (mm)	60
d	110 mm
D	170 mm
T	60 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	4.504
EAN	4547359454697
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7 ISO P4
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	45 Degree
Preload	Light
Raceway Style	Not Applicable
Cage Material	Brass
Rolling Element	Ball Bearing
Mounting Arrangement	Universal

Flush Ground	Yes
Inch – Metric	Metric
Other Features	Double Row Angular Contact Thrust Bearing Double Direction
Long Description	120MM Bore; 180MM Outside Diameter; 60MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Bal
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword 3	Thrust
Keyword String	Ball Angular Contact Thrust
Manufacturer Item Number	742024/GNP4
Weight / LBS	9.921
Bore	4.724 Inch 120 Millimeter
Width	2.362 Inch 60 Millimeter
Outside Diameter	7.087 Inch 180 Millimeter
bore diameter:	120 mm
dynamic load capacity:	87000 N
outside diameter:	180 mm
operating temperature range:	-40 to 120 °C
overall width:	60 mm
maximum rpm:	3800 rpm
thrust bearing type:	Double-Direction
bearing material:	High Carbon Chrome Steel
outside diameter design:	Straight
cage material:	Brass
separable or banded:	Separable

fillet radius:	2 mm
precision rating:	ISO Class 4
series:	742
static load capacity:	223000 N
manufacturer product page:	Click here