

LS GEEW12ES-2RS plain bearings

Manufacturers of all are represented in 90 Outer Diameter (mm) our partial list of clients. Contact Gary for a complete LS GEEW12ES-2RS plain bearings list 40x90x23 Size (mm) of clients and projects.

Size (mm)	40x90x23
Bore Diameter (mm)	40
Outer Diameter (mm)	90
Width (mm)	23
d	40 mm
D	90 mm
B	23 mm
C	23 mm
rn	0,5 mm
r min.	1,5 mm
da min.	48 mm
da max	54 mm
Da max.	82 mm
ra max.	1,5 mm
Weight	0,63 Kg
Basic dynamic load rating (C)	40,5 kN
Basic static load rating (C0)	24 kN
(Grease) Lubrication Speed	7 800 r/min
Inventory	2.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A

Weight / Kilogram	0.64
EAN	4547359005561
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6308ZZ
Weight / LBS	1.401
Outer Race Width	0.906 Inch 23 Millimeter
Bore	1.575 Inch 40 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
bore diameter:	40 mm
precision rating:	ISO Class 0
outside diameter:	90 mm
finish/coating:	Uncoated
overall width:	23 mm

bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	23 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	23 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	7800 rpm
internal clearance:	CN
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	9200 RPM
dynamic load capacity:	40500 N
series:	63
static load capacity:	24000 N
manufacturer product page:	Click here