

LS GEFZ22S plain bearings

Can't find what you're looking for 110 mm da LS GEFZ22S plain bearings ? Our expert Representatives be in contact with you shortly!

da	110 mm
db	123.825 mm
dc	106.362 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	165.1 mm
S	4.763 mm
ba	50.006 mm
H	239.316 mm
H1	125.425 mm
H2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	45.244 mm
Housing	SAF 222

Bearing	22222 E
Lock nut	AN 22
Lock washer	W 22
Stabilizing ring	SR-22-19
Labyrinth ring (db shaft position)	LOR 121
PosiTrac Plus contact element (db shaft position)	B10724-122
Labyrinth ring (dc shaft position)	LOR 113
PosiTrac Plus contact element (dc shaft position)	B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1150 r/min
P60°	149 kN
P90°	89 kN
P120°	55.6 kN
P150°	50.7 kN
P180°	60.9 kN
Pa	39.6 kN
Mass pillow block	30.7 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	481.95 g