

LS GEH220XF/Q plain bearings

YOU'LL FIND AN EXTENSIVE SELECTION OF LS GEH220XF/Q plain bearings Mounted Bearing Engineering Group FOR SALE.

| | |
|--------------------------|--------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 2-11/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QVVC16V211SB |
| Locking Style | Double V-Lock |
| Weight | 22.00 lb |
| Housing Style | Piloted Flange Cartridge |
| UPC Code | 0883450063210 |
| Dimension BC | 7.50 in |
| Dimension C | 4.190 in |
| Dimension E | 5.30 in |
| Dimension B Fix | 2.08 in |
| Dimension B Exp | 2.16 in |
| Dimension F | 8.75 in |
| Dimension D | 6.38 in |
| Dimension H | 0.81 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension L | 3.33 in |
| Dimension RVV | 0.76 in |
| Dimension SVV | 4.08 in |
| Dimension G | 6.375 in |
| Dimension N | 1.25 in |
| C – Dynamic Load (Basic) | 57200 lb |
| C0 – Static Load | 62500 lb |

| | |
|-------------------------------------|-----------|
| e – Geometry Factor | 0.22 |
| Y1 – Geometry Factor | 3.14 |
| Y2 – Geometry Factor | 4.67 |
| Oil Lubrication – M/N Seal | 1500 rpm |
| Oil Lubrication – T Seal | 2650 rpm |
| Oil Lubrication – B/C/O Seal | 1200 rpm |
| Grease Lubrication – M/N Seal | 1500 rpm |
| Grease Lubrication – T Seal | 2200 rpm |
| Grease Lubrication – B/C/O Seal | 1150 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0020 in |
| Eng Internal Radial Clearance – Min | 0.0037 |
| Eng Internal Radial Clearance – Max | 0.0047 |
| Pre Install Clearance Min | 0.0037 in |
| Pre Install Clearance Max | 0.0047 in |