

LS GX140S plain bearings

LET OUR LS GX140S plain bearings 190.5 mm da EXPERTS GET YOU THE PARTS YOU NEED.

da	190.5 mm
Da	399.999 mm
Ca	117.805 mm
A1	222.25 mm
A2	304.8 mm
S	4.763 mm
ba	90.487 mm
H	474.663 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	79.375 mm
Housing	SAFS 544
Bearing	22244 CCK/W33
Adapter sleeve assembly	SNW 44×7.1/2
Stabilizing ring	SR-44-38

Labyrinth ring	2 x LOR 584
PosiTrac Plus contact element	2 x B10724-167
End plug (suffix Y)	EPR 23
Max. speed for PosiTrac Plus seal	725 r/min
P60°	691 kN
P90°	414 kN
P120°	260 kN
P150°	236 kN
P180°	285 kN
Pa	71.2 kN
Mass pillow block	262 kg
Cap bolt	1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g