

NACHI 22226EX cylindrical roller bearings

Online shopping NACHI 22226EX cylindrical roller bearings from a great selection at Store. ... Accessories. 850x600x254 Size (mm)

| | |
|---------------------|-------------|
| Size (mm) | 850x600x254 |
| Bore Diameter (mm) | 850 |
| Outer Diameter (mm) | 600 |
| Width (mm) | 254 |
| d1 | 600 mm |
| D | 850 mm |
| B1 | 254 mm |
| d2 | 699 mm |
| d3 | 730 mm |
| D1 | 785 mm |
| B | 165 mm |
| B2 | 75 mm |
| B5 | 97 mm |
| s1 | 35.5 mm |
| r1,2 – min. | 6 mm |
| da – max. | 723 mm |
| db – min. | 650 mm |
| Da – min. | 766 mm |
| Da – max. | 827 mm |
| Ba – min. | 22 mm |
| Ca – min. | 2.4 mm |
| ra – max. | 5 mm |

| | |
|-------------------------------|-----------|
| Basic dynamic load rating – C | 4650 kN |
| Basic static load rating – C0 | 10000 kN |
| Fatigue load limit – Pu | 640 kN |
| Reference speed | 530 r/min |
| Limiting speed | 700 r/min |
| Factor – k1 | 0.121 |
| Factor – k2 | 0.11 |
| d2 ≈ | 699 mm |
| D1 ≈ | 785 mm |
| s1 max. | 35.5 mm |
| r1,2 min. | 6 mm |
| da max. | 723 mm |
| db min. | 650 mm |
| Da min. | 766 mm |
| Da max. | 827 mm |
| Ba min. | 22 mm |
| Ca min. | 2.4 mm |
| ra max. | 5 mm |
| Basic dynamic load rating C | 4650 kN |
| Basic static load rating C0 | 10000 kN |
| Fatigue load limit Pu | 640 kN |
| Misalignment factor k1 | 0.121 |
| Operating clearance factor k2 | 0.11 |
| Mass bearing + sleeve | 420 kg |