

# NACHI 22320EX cylindrical roller bearings

NACHI 22320EX cylindrical roller bearings 0.0 Inventory Product Brochures , Manufacturing Service . Get SKF Manufacturer Name Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | SKF  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 1.63   |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | YAR 207-104-2F   |
| Seals                     | M Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Standard Duty   Wide Inner Race   Low Base   Has Flinger                      |
| Long Description          | 2 Bolt Pillow Block; 1-1/4" Bore; 1-13/16" Base to Center Height; Set Screw Mount; Ball Be |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | SYH 1.1/4 TF                   |
| Weight / LBS                  | 3.6                            |
| Bolt Spacing Maximum          | 5.25 Inch   133.35Millimeter   |
| Nominal Bolt Center to Center | 5 Inch   127 Millimeter        |
| B                             | 1.813 Inch   46.05 Millimeter  |
| d                             | 1.25 Inch   31.75 Millimeter   |
| D                             | 1.688 Inch   42.87 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| Bolt Spacing Minimum          | 4.688 Inch   119.075Millimeter |