

NACHI 35BVV07X-6 angular contact ball bearings

Offer High Quality Brand NACHI 35BVV07X-6 angular contact ball bearings .Contact Us Online to Get Best Quote. 60x130x46 Size (mm)

Size (mm)	60x130x46
Bore Diameter (mm)	60
Outer Diameter (mm)	130
Width (mm)	46
d	60 mm
Fw	77 mm
D	130 mm
B	46 mm
C	46 mm
r min.	2,1 mm
r1 min.	2,1 mm
Weight	2,71 Kg
Basic dynamic load rating (C)	169 kN
Basic static load rating (C0)	188 kN
(Grease) Lubrication Speed	4 800 r/min
E	113 mm
F	77 mm
rs min	2.1 mm
r1s min	2.1 mm
Radial clearance class	CN
Mass (without HJ ring)	2.7 kg
Dynamic load, C	169 kN

Static load, C0	188 kN
Fatigue limit load, Cu	22.9 kN
Nlim (oil)	5,700 rpm
Nlim (grease)	4,800 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	71 mm
da max	75 mm
db min	79 mm
Da max	119 mm
ra max	2 mm
rla max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	2.647
EAN	4547359143720
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes

Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage On Outer Ring ID
Long Description	60MM Bore; Straight Bore Profile; 130MM Outside Diameter; 46MM Width; Steel Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU2312
Weight / LBS	5.846
Width	1.811 Inch 46 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
Bore	2.362 Inch 60 Millimeter
bore diameter:	60 mm
static load capacity:	188000 N
outside diameter:	130 mm
precision rating:	ISO Class 0
overall width:	46 mm
maximum rpm:	5700 rpm
flanges:	(2) Outer Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	Pressed Steel
number of rows:	1
finish/coating:	Uncoated
internal clearance:	CN

closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	2 mm
operating temperature range:	-40 to 120 °C
manufacturer product page:	Click here
dynamic load capacity:	169000 N