

NACHI 53430U thrust ball bearings

170 Million used NACHI 53430U thrust ball bearings 130 mm da instantly searchable. 149.225 mm db Shop our large selection of parts based on brand, price, description, and location. Order the with stock 125.412 mm dc ...

da	130 mm
db	149.225 mm
dc	125.412 mm
Da	230 mm
Ca	89.789 mm
A1	133.35 mm
A2	193.675 mm
S	4.763 mm
ba	65.881 mm
H	295.275 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm
L	466.725 mm
N1	25.4 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT

h	52.388 mm
Housing	SAW 226
Bearing	23226 CC/W33
Lock nut	AN 26
Lock washer	W 26
Stabilizing ring	SR-26-0
Labyrinth ring (db shaft position)	LOR 136
Labyrinth ring (dc shaft position)	LOR 122
End plug (suffix Y)	EPR 27
Bearing limiting speed	2600 r/min
P60°	189 kN
P90°	113 kN
P120°	73.8 kN
P150°	68.1 kN
P180°	84.5 kN
Pa	31.2 kN
Mass pillow block	61.2 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g