

NACHI 53430U thrust ball bearings

170 Million used NACHI 53430U thrust ball bearings 130 mm da instantly searchable. 149.225 mm db Shop our large selection of parts based on brand, price, description, and location. Order the with stock 125.412 mm dc ...

| | |
|--------|------------|
| da | 130 mm |
| db | 149.225 mm |
| dc | 125.412 mm |
| Da | 230 mm |
| Ca | 89.789 mm |
| A1 | 133.35 mm |
| A2 | 193.675 mm |
| S | 4.763 mm |
| ba | 65.881 mm |
| H | 295.275 mm |
| H1 | 152.4 mm |
| H2 | 60.325 mm |
| J min. | 371.475 mm |
| J max. | 406.4 mm |
| J1 | 82.55 mm |
| L | 466.725 mm |
| N1 | 25.4 mm |
| R1 | 79.375 mm |
| R2 | 36.513 mm |
| RG | 1/2 NPT |
| PG | 1/4 NPT |

| | |
|--|--------------|
| h | 52.388 mm |
| Housing | SAW 226 |
| Bearing | 23226 CC/W33 |
| Lock nut | AN 26 |
| Lock washer | W 26 |
| Stabilizing ring | SR-26-0 |
| Labyrinth ring (db shaft position) | LOR 136 |
| Labyrinth ring (dc shaft position) | LOR 122 |
| End plug (suffix Y) | EPR 27 |
| Bearing limiting speed | 2600 r/min |
| P60° | 189 kN |
| P90° | 113 kN |
| P120° | 73.8 kN |
| P150° | 68.1 kN |
| P180° | 84.5 kN |
| Pa | 31.2 kN |
| Mass pillow block | 61.2 kg |
| Cap bolt | 2 x 1-8 UNC |
| Cap bolt recommended tightening torque | 400 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 3/8-16 UNC |
| Appropriate attachment bolt size G | 0.875 in |
| Initial grease fill | 382.73 g |