

# NACHI 54210 thrust ball bearings

Online shopping NACHI 54210 thrust ball bearings from 0.0 Inventory a great selection at Store. ... Accessories.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	14 lb
EAN	0053893778297
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only – Half Round Top Angle
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row   Double Collar   Two Lip Seal   Electrodeposition Coating   With Set Screw
Inch – Metric	Inch
Long Description	Take Up Bearing Only; 1-15/16" Bore; Tapered Roller Bearing; Unit Only – Half Round Top Angle;
UNSPSC	31171533
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing

Keyword String	Take Up
Manufacturer Item Number	E-TTU-TRB-1 15/16
Weight / LBS	13.76
Slot Width	0 Inch   0 Millimeter
Slot to Slot Distance	0 Inch   0 Millimeter
d	1.938 Inch   49.225 Millimeter
Shaft Size	1.9375 in
Shaft Size Type	Imperial
UPC Code	053893778297
Dimension B	3-1/2 in
Dimension H	6-3/8 in
Dimension H1	5-3/16 in
Dimension H2	2.39 in
Dimension d1	3-7/16 in
Dimension A	1-3/4 in
Dimension A1	1-3/4 in
Housing Width	2-9/16 in
Dimension L	6-1/2 in
Dimension L1	6 in
Dimension L2	3.4 in
e	0.33
X (if $F_a/F_r \leq e$ )	0.87
Y (if $F_a/F_r \leq e$ )	2.64
X (if $F_a/F_r > e$ )	0.7
Y (if $F_a/F_r > e$ )	3.18
K Factor	1.83
C90 Dynamic Load Rating <sub>1</sub>	10300 lb
C0 Static Load Rating	43000 lb

Fa-max Maximum Permissible Thrust Load <sup>2</sup>	2590 lb
Fr-max Maximum Allowable Slip Fit Radial Load <sup>3</sup>	8400 lb
Max. Speed <sup>4</sup>	3050 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to