

NACHI 54216U thrust ball bearings

High Quality 139,7 Bore Diameter (mm) NACHI 54216U thrust ball bearings. Competitive Pricing. Accept Small Order. Easy 139.7×63.5×31.75 Size (mm) and Fast Shipping.

Size (mm)	139.7×63.5×31.75
Bore Diameter (mm)	139,7
Outer Diameter (mm)	63,5
Width (mm)	31,75
d	63.5 mm
D	139.7 mm
B	31.75 mm
d1	91 mm
E	121.5 mm
r1,2 – min.	3.2 mm
r3,4 – min.	3.2 mm
s	2 mm
da – min.	78 mm
da – max.	119 mm
Da – min.	123 mm
Da – max.	126 mm
ra – max.	3 mm
rb – max.	3 mm
Basic dynamic load rating – C	138 kN
Basic static load rating – C0	143 kN
Fatigue load limit – Pu	18.3 kN
Reference speed	5300 r/min

Limiting speed	6300 r/min
Calculation factor – kr	0.12
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.212
EAN	7316577014009
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Outer Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Inch
Other Features	2 Rib Inner Ring Plain Outer Ring Cage on Inner Ring OD
Long Description	2-1/2" Bore; Straight Bore Profile; 5-1/2" Outside Diameter; 1-1/4" Width; Steel Cage
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing

Keyword String	Cylindrical
Manufacturer Item Number	CRM 20 A
Weight / LBS	4.877
Width	1.25 Inch 31.75 Millimeter
Outside Diameter	5.5 Inch 139.7 Millimeter
Bore	2.5 Inch 63.5 Millimeter
d1 ≈	91 mm
r1,2 min.	3.2 mm
r3,4 min.	3.2 mm
s max.	2 mm
da min.	78 mm
da max.	119 mm
Da min.	123 mm
Da max.	126 mm
ra max.	3 mm
rb max.	3 mm
Basic dynamic load rating C	138 kN
Basic static load rating C0	143 kN
Fatigue load limit Pu	18.3 kN
Calculation factor kr	0
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	2.15 kg