

# NACHI 6013NKE deep groove ball bearings

Find the discount NACHI 6013NKE deep groove ball bearings online you need . We offer ... If you check 0.0 Inventory out our large selection of NACHI 6013NKE deep groove ball bearings once .

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN                                      |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 17.706                                      |
| EAN                       | 0883450319706                               |
| Product Group             | M06288                                      |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar                           |
| Housing Style             | 2 Bolt Pillow Block                         |
| Rolling Element           | Spherical Roller Bearing                    |
| Housing Material          | Cast Steel                                  |
| Expansion / Non-expansion | Non-expansion                               |
| Mounting Bolts            | 7/8 Inch                                    |
| Relubricatable            | Yes   |
| Insert Part Number        | 22218                                       |
| Seals                     | Triple Lip Viton                            |
| Housing Configuration     | 1 Piece Solid                               |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Double Collar   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 3-1/4" Bore;<br>3-3/4" Base to Center Height;<br>Concentric Collar Mount; S |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Weight / LBS                  | 45   |
| B                             | 3.75 Inch   95.25 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| d                             | 3.25 Inch   82.55 Millimeter   |
| Bolt Spacing Minimum          | 9.375 Inch   238.125Millimeter   |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter   |
| D                             | 5.18 Inch   131.572 Millimeter   |
| Bolt Spacing Maximum          | 11.25 Inch   285.75Millimeter  |