

# NACHI 60KDE13 tapered roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your NACHI 60KDE13 tapered roller bearings needs – 1.3750 in d including routine maintenance, 6.8750 in overall length: major repairs, warranty service, and equipment inspections.

d	1.3750 in
expansion type:	Non-Expansion Bearing (Fixed)
overall length:	6.8750 in
finish/coating:	Uncoated
overall height:	3.8400 in
B	2.63 in
mounting:	Two-Bolt Base
seal type:	Triple Lip
bearing type:	Spherical Roller
radial dynamic load capacity:	20800 lb
bore type:	Round
radial static load capacity:	21000 lb
housing construction:	Solid Pillow Block
maximum rpm:	3975 RPM
base to bore centerline:	1.8750 in
lubrication type:	Lubrication Fitting
housing material:	Steel
series:	HD
locking device:	Adapter Mount

standards met:	UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA, ASTM A-27 Grade 70-36 Class 1UL AFBMA AGMA ASMMA BSA
D	4.69 to 5.88 in
replacement bearing:	22208
base width:	2-1/4 in
manufacturer catalog number:	071864