

# NACHI 6214ZZE deep groove ball bearings

We Provide Extensive 40 mm d NACHI 6214ZZE deep groove ball bearings 40 Bore Diameter (mm) Selection And Competitive Wholesale Pricing. 88.9 mm Da

|                               |          |
|-------------------------------|----------|
| Bore Diameter (mm)            | 40       |
| d                             | 40 mm    |
| Da                            | 88.9 mm  |
| s1                            | 34.9 mm  |
| A1                            | 14 mm    |
| B1                            | 56.3 mm  |
| G                             | 12 mm    |
| H                             | 171,5 mm |
| J                             | 143,5 mm |
| L                             | 102 mm   |
| N                             | 14 mm    |
| T                             | 58,9 mm  |
| A2                            | 14 mm    |
| Weight                        | 1,8 Kg   |
| Basic dynamic load rating (C) | 30,7 kN  |
| Basic static load rating (C0) | 19 kN    |
| Fatigue load limit (Pu)       | 0,8      |
| Inventory                     | 0.0      |
| Manufacturer Name             | SKF      |
| Minimum Buy Quantity          | N/A      |
| Weight / Kilogram             | 0        |
| Product Group                 | M06110   |

|   |               |
|---|---------------|
| Housing material                                  | Cast iron     |
| Db1   | 98 mm         |
| Db2   | 102 mm        |
| A   | 38.5 mm       |
| A3  | 3.2 mm        |
| A5  | 23.5 mm       |
| B4  | 6.75 mm       |
| RG  | 1/4-28 UNF    |
| R1  | 24.5 mm       |
| R $\alpha$  | 45 °          |
| DN  | 6.5 mm        |
| SWN   | 7 mm          |
| GN  | 1/4-28 SAE-LT |
| J6  | 115.5 mm      |
| J7  | 16 mm         |
| N4  | 2 mm          |
| Basic dynamic load rating C                       | 30.7 kN       |
| Basic static load rating C0                       | 19 kN         |
| Fatigue load limit Pu                             | 0.8 kN        |
| Limiting speed                                    | 4800 r/min    |
| Mass bearing unit                                 | 1.65 kg       |
| Thread grub screw G2                              | M10x1         |
| Hexagonal key size for grub screw N               | 5 mm          |
| Recommended tightening torque for grub screw      | 16.5 N·m      |
| Recommended diameter for attachment bolts, mm G   | 12 mm         |
| Recommended diameter for attachment bolts, inch G | 0.5 in        |
| Housing   | FYTB 508 M    |
| Bearing   | YEL 208-2F    |

End cover

ECY 208