

# NACHI 7210DT angular contact ball bearings

LET OUR NACHI 7210DT angular contact ball bearings EXPERTS 0.0 Inventory GET YOU THE PARTS YOU NEED.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 10.624  |
| EAN                       | 0698210642457   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Round Flange Cartridge   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 2211U   |
| Seals                     | Light Contact   |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Round Flange Cartridge; 2-11/16" Bore; 7-1/2" Bolt Circle; 5-19/64" Bolt Spaci |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Double Row   Single Collar   With Set Screw |
| UNSPSC                             | 31171501                                    |
| Harmonized Tariff Code             | 8483.20.40.80                               |
| Noun                               | Bearing                                     |
| Keyword String                     | Flanged                                     |
| Manufacturer Item Number           | KBR2211                                     |
| Manufacturer Internal Number       | 6864245                                     |
| Weight / LBS                       | 23.4  |
| Cartridge Pilot Depth              | 1.25 Inch   31.75 Millimeter                |
| D                                  | 4 Inch   101.6 Millimeter                   |
| Bolt Spacing                       | 5.297 Inch   134.544 Millimeter             |
| Nominal Bolt Circle Diameter Round | 7.5 Inch   190 Millimeter                   |
| Cartridge Pilot Diameter           | 6.375 Inch   161.92 Millimeter              |
| d                                  | 2.688 Inch   68.275 Millimeter              |