

NACHI 7217AC angular contact ball bearings

Our highly-skilled and factory-trained 0.0 Inventory service experts have the resources to help you with all your NACHI 7217AC angular contact ball bearings needs SKF Manufacturer Name – including routine maintenance, major repairs, warranty service, and equipment inspections.

| | |
|------------------------------|--------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 2.487 |
| EAN | 7316577732590 |
| Product Group | B04334 |
| bore diameter: | 140 mm |
| dynamic load capacity: | 194 kN |
| cup width: | 21 mm |
| static load capacity: | 325 kN |
| assembly type: | Cone & Cup |
| finish/coating: | Uncoated |
| outside diameter: | 195 mm |
| maximum rpm: | 3200 RPM |
| cone width: | 27 mm |
| series: | T4CB |
| closure type: | Open |
| flange type: | Non-Flanged Cup |
| operating temperature range: | Maximum of +250 °F |
| Dimension series | 4CB |

| | |
|-----------------------------|------------|
| d | 140 mm |
| D | 195 mm |
| T | 29 mm |
| d1 ≈ | 165.9 mm |
| B | 27 mm |
| C | 21 mm |
| r1,2 min. | 3 mm |
| r3,4 min. | 3 mm |
| a | 40.41 mm |
| da max. | 150 mm |
| db min. | 154 mm |
| Da min. | 180 mm |
| Da max. | 182 mm |
| Db min. | 189 mm |
| Ca min. | 6 mm |
| Cb min. | 8 mm |
| ra max. | 3 mm |
| rb max. | 3 mm |
| Basic dynamic load rating C | 241 kN |
| Basic static load rating C0 | 325 kN |
| Fatigue load limit Pu | 33.5 kN |
| Reference speed | 2400 r/min |
| Limiting speed | 3000 r/min |
| Calculation factor e | 0.5 |
| Calculation factor Y | 1.2 |
| Calculation factor Y0 | 0.7 |
| Mass bearing | 2.4 kg |