

NACHI 99587/99100 tapered roller bearings

170 Million 168.275 mm db used NACHI 99587/99100 tapered roller bearings instantly searchable. Shop our large selection of parts 150 mm da based on brand, price, description, and location. Order the with stock ...

da	150 mm
db	168.275 mm
dc	146.05 mm
Da	269.999 mm
Ca	82.804 mm
A1	158.75 mm
A2	215.9 mm
S	4.763 mm
ba	65.088 mm
H	317.5 mm
H1	160.35 mm
H2	63.5 mm
L	539.75 mm
R1	95.25 mm
R2	39.688 mm
RG	3/4 NPT
PG	1/4 NPT
h	50.8 mm
Housing	SSAFS 230
Bearing	22230 CC/W33
Lock nut	AN 30

Lock washer	W 30
Stabilizing ring	SR-30-0
Labyrinth ring (db shaft position)	LOR 151
PosiTrac Plus contact element (db shaft position)	B10724-151
Labyrinth ring (dc shaft position)	LOR 134
PosiTrac Plus contact element (dc shaft position)	B10724134-
End plug (suffix Y)	EPR 17
Max. speed for PosiTrac Plus seal	850 r/min
P60°	394 kN
P90°	236 kN
P120°	149 kN
P150°	136 kN
P180°	162 kN
Pa	105 kN
Mass pillow block	110 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	623.7 g