

NACHI E30208J tapered roller bearings

What are the 360x260x46 Size (mm) dimensions of a NACHI E30208J tapered roller bearings? Manufacturing Service . Get Your Free, Instant Quote

Size (mm)	360x260x46
Bore Diameter (mm)	360
Outer Diameter (mm)	260
Width (mm)	46
d	260 mm
D	360 mm
B	46 mm
d1	291.9 mm
D1	329.3 mm
r1,2 – min.	2.1 mm
da – min.	270 mm
Da – max.	350 mm
ra – max.	2 mm
Basic dynamic load rating – C	212 kN
Basic static load rating – C0	270 kN
Fatigue load limit – Pu	6.6 kN
Reference speed	3600 r/min
Limiting speed	3000 r/min
Calculation factor – kr	0.02
Calculation factor – f0	16.5
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	14.81
EAN	7316577095428
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Brass
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	260MM Bore; 360MM Outside Diameter; 46MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61952 MA
Weight / LBS	32.61
Outside Diameter	14.173 Inch 360 Millimeter
Bore	10.236 Inch 260 Millimeter
Outer Race Width	1.811 Inch 46 Millimeter
bore diameter:	260 mm
static load capacity:	270 kN
outside diameter:	360 mm
precision rating:	Not Rated

overall width:	46 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Brass
closure type:	Open
outer ring width:	46 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
snap ring included:	Without Snap Ring
maximum rpm:	3000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	212 kN
d1 ≈	291.9 mm
D1 ≈	329.3 mm
r1,2 min.	2.1 mm
da min.	270 mm
Da max.	350 mm
ra max.	2 mm
Basic dynamic load rating C	212 kN
Basic static load rating C0	270 kN
Fatigue load limit Pu	6.55 kN
Calculation factor kr	0.02
Calculation factor f0	16.5
Mass bearing	14.4 kg