

NACHI E32928J tapered roller bearings

With over 10170 full-service stores, 37 mm D our NACHI E32928J tapered roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize 12 mm d your productivity by saving time and your hard-earned dollars.

| | |
|---|------------|
| d | 12 mm |
| D | 37 mm |
| B | 12 mm |
| rs min | 1 mm |
| Radial clearance class | C3 |
| Mass | 0.06 kg |
| Dynamic load, C | 9.7 kN |
| Static load, C0 | 4.2 kN |
| Fatigue limit load, Cu | 0.19 kN |
| f0 | 11.1 |
| Nlim (grease) | 20,000 rpm |
| Min operating temperature, Tmin | -25 °C |
| Max operating temperature, Tmax | 110 °C |
| Characteristic cage frequency, FTF | 0.34 Hz |
| Characteristic rolling element frequency, BSF | 2.76 Hz |
| Characteristic outer ring frequency, BPF0 | 2.03 Hz |
| Characteristic inner ring frequency, BPFI | 3.97 Hz |

| | |
|---------------------------------|---|
| da min | 17 mm |
| da max | 18.5 mm |
| Da max | 32 mm |
| ra max | 1 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.06 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Non-Contact Seal |
| Internal Clearance | C3-Loose |
| Inch – Metric | Metric |
| Long Description | 12MM Bore; 37MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No |
| Other Features | Deep Groove Non-Friction Nitrile Rubber Seal Prelubricated |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |

| | |
|------------------|----------------------------|
| Keyword String | Ball |
| Weight / LBS | 0.13227 |
| Outer Race Width | 0.472 Inch 12 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore | 0.472 Inch 12 Millimeter |
| Outside Diameter | 1.457 Inch 37 Millimeter |