

NACHI H-26878R/H-26822 tapered roller bearings

Various types and sizes to 40x80x18 Size (mm) accommodate your NACHI H-26878R/H-26822 tapered roller bearings 40 Bore Diameter (mm) requirements.

Size (mm)	40x80x18
Bore Diameter (mm)	40
Outer Diameter (mm)	80
Width (mm)	18
d	40 mm
D	80 mm
B	18 mm
C	18 mm
Angle (α)	40 °
a	34.2 mm
r min.	1.1 mm
r1 min.	0.6 mm
da min.	47 mm
Da max.	73 mm
ra max.	1 mm
Weight	0.382 Kg
(Grease) Lubrication Speed	7500 r/min
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0605790367939

Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Bal
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Width	0.709 Inch 18 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Bore	1.575 Inch 40 Millimeter
Bearing No.	7208B
r(min)	1.1
r1(min)	0.6
Cr	40.2
C0r	23.0
Cu	1.40

f ₀	—
Grease lub.	6000
Oil lub.	8000
a(mm)	34.2
d _a (min)	47
D _a (max)	73
r _a (max)	1
(Refer.) Mass (kg)	0.382