

# NACHI H-E32305J tapered roller bearings

How do I place an N/A Minimum Buy Quantity EMERGENCY order for a NACHI H-E32305J tapered roller bearings that I want to pick up at a our 0.0 Inventory store?

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.03
EAN	7316577002501
Product Group	B04286
Stud Profile	Male
Mounting Thread	M8 X 1.25
Thread Direction	Right Hand
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Steel
Relubricatable	No
Enclosure	Open
Other Features	3 Piece   Zinc Plated Outer
Long Description	8MM Bore; 6.5MM House Width; Male Stud Profile; M8 X 1.25; Right Hand Thread Direction; Spherical Pl
Inch – Metric	Metric
UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55

Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer Item Number	SA 8 E
Weight / LBS	0.064
Housing Width	0.256 Inch   6.5 Millimeter
Ball Width	0.315 Inch   8 Millimeter
d	8 mm
bore diameter:	8 mm
ball material:	Steel
misalignment angle:	15 °
race material:	Steel
shank thread length:	21 mm
radial static load capacity:	12.9 kN
rod end type:	Male Threaded
operating temperature range:	-30 to +130 °F
shank thread size:	M8x1.25
head diameter:	25 mm
thread direction:	Right Hand
head width:	6.5 mm
grade:	Commercial/Industrial
ball width:	8 mm
lubrication type:	No Fitting
length to ball center:	42 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998
d2 max.	25 mm
B	8 mm
G	M 8

C1 max.	6.5 mm
h	42 mm
$\alpha$	15 °
dk	13 mm
l1 min.	21 mm
l2 max.	56 mm
l7 min.	11 mm
r1 min.	0.3 mm
Basic dynamic load rating C	5.5 kN
Basic static load rating C0	12.9 kN
Specific dynamic load factor K	100 N/mm <sup>2</sup>
Material constant KM	330
Mass rod end	0.029 kg