

# NACHI NF 1013 cylindrical roller bearings

YOU'LL FIND AN 0.0 Inventory EXTENSIVE SELECTION OF N/A Minimum Buy Quantity NACHI NF 1013 cylindrical roller bearings FOR SALE.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REGAL BELOIT  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.681   |
| EAN                       | 0662461234945   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 13/32 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 2-012C-CR   |
| Seals                     | Single Lip Contact  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Square Flange Block;<br>3/4" Bore; 3-1/2" Bolt Circle;<br>2-1/2" Bolt Spacing; 1 Pie |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Standard Duty   Corrosion Resistant   Has Flinger |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | SF-12C CR  |
| Manufacturer Internal Number       | 723534   |
| Weight / LBS                       | 1.5  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter  |
| D                                  | 1.219 Inch   30.96 Millimeter                                  |
| Nominal Bolt Circle Diameter Round | 3.5 Inch   90 Millimeter                                       |
| d                                  | 0.75 Inch   19.05 Millimeter                                   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter  |
| Bolt Spacing                       | 2.5 Inch   63.5 Millimeter                                     |