NACHI NJ 2305 E cylindrical roller bearings

Manufacturers of all are represented in our partial list of 3-3/4 in base width: clients. 2.9375 in d Contact Gary for a complete NACHI NJ 2305 E cylindrical roller bearings list of clients and projects.

d2.9375 inbase width:3-3/4 inoverall length:10.4375 inexpansion type:Expansion Bearing (Floating)overall height:6.4375 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing device:Concentric Collarseries:2000D8-1/8 in		
overall length:10.4375 inexpansion type:Expansion Bearing (Floating)overall height:6.4375 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing device:Concentric Collarseries:2000	d	2.9375 in
expansion type:Expansion Bearing (Floating)overall height:6.4375 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:2000	base width:	3-3/4 in
overall height:6.4375 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:2000	overall length:	10.4375 in
finish/coating:Powder Coatedmounting:Four-Bolt BaseB4 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:2000	expansion type:	Expansion Bearing (Floating)
mounting:Four-Bolt BaseB4 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:2000	overall height:	6.4375 in
B4 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:2000	finish/coating:	Powder Coated
bearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:2000	mounting:	Four-Bolt Base
seal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:2000	В	4 in
bore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:2000	bearing type:	Spherical Roller
radial dynamic load capacity: 46800 lb housing construction: Solid Pillow Block radial static load capacity: 55700 lb base to bore centerline: 3.2500 in maximum rpm: 1700 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Concentric Collar series: 2000	seal type:	Contact/Lip
housing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:2000	bore type:	Round
radial static load capacity: 55700 lb base to bore centerline: 3.2500 in maximum rpm: 1700 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Concentric Collar series: 2000	radial dynamic load capacity:	46800 lb
base to bore centerline:3.2500 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:2000	housing construction:	Solid Pillow Block
maximum rpm: 1700 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Concentric Collar series: 2000	radial static load capacity:	55700 lb
housing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:2000	base to bore centerline:	3.2500 in
Iubrication type:Lubrication Fittinglocking device:Concentric Collarseries:2000	maximum rpm:	1700 RPM
locking device: Concentric Collar 2000	housing material:	Cast Iron
series: 2000	lubrication type:	Lubrication Fitting
	locking device:	Concentric Collar
D 8-1/8 in	series:	2000
	D	8-1/8 in

standards met: ANSI/ABMA STD 9-1990	
-------------------------------------	--