

NACHI NN3018K cylindrical roller bearings

NACHI NN3018K cylindrical roller bearings Product Brochures , Manufacturing 98.4 mm Da Service . 42.862 mm d Get Your Free. Cast iron Housing material

Housing material	Cast iron
d	42.862 mm
Da	98.4 mm
Db1	102 mm
Db2	111 mm
A	39 mm
A1	14 mm
A3	3.2 mm
A5	26.5 mm
B	49.2 mm
B4	8 mm
J	148.5 mm
H	178.5 mm
L	111 mm
N	16 mm
s1	30.2 mm
T	54.2 mm
RG	1/4-28 UNF
R1	24.5 mm
R α	45 °
DN	6.5 mm
SWN	7 mm

GN	1/4-28 SAE-LT
J6	120.5 mm
J7	18 mm
N4	2 mm
Basic dynamic load rating C	33.2 kN
Basic static load rating C0	21.6 kN
Fatigue load limit Pu	0.915 kN
Limiting speed	4300 r/min
Thread grub screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	14 mm
Recommended diameter for attachment bolts, inch G	0.5625 in
Housing	FYTB 509 M
Bearing	YAR 209-111-2F
End cover	ECY 209