

NACHI NP 217 cylindrical roller bearings

100% Authentic. NACHI NP 217 cylindrical roller bearings Highest Quality. Certified 45 Bore Diameter (mm) 105 mm Da Supplier.

Bore Diameter (mm)	45
d	45 mm
Da	105 mm
s1	30.2 mm
A1	14 mm
B	49,2 mm
G	14 mm
J	132 mm
L	160 mm
N	16 mm
T	40,2 mm
A2	14 mm
A3	12 mm
J1	93.3 mm
Weight	2,65 Kg
Basic dynamic load rating (C)	33,2 kN
Basic static load rating (C0)	21,6 kN
Fatigue load limit (Pu)	0,915
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.882

EAN	7316570516449
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	14 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 209-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch – Metric	Metric
Long Description	4 Bolt Round Flange Cartridge; 45MM Bore; 132MM Bolt Circle; 93.3MM Bolt Spacing; 1 Piece Solid; Set
Other Features	Single Row Wide Inner Race Open End Has Flinger Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FYC 45 TF
Weight / LBS	5.84

Length Thru Bore	1.937 Inch 49.2 Millimeter
Nominal Bolt Circle Diameter Round	5.2 Inch 132 Millimeter
Bore	1.772 Inch 45 Millimeter
Cartridge Pilot Depth	0.472 Inch 12 Millimeter
Bolt Spacing	3.673 Inch 93.3 Millimeter
Cartridge Pilot Diameter	4.134 Inch 105 Millimeter
bore diameter:	45 mm
radial static load capacity:	21.6 kN
bolt circle diameter:	132 mm
length through bore:	49.2 mm
overall length/diameter:	160 mm
finish/coating:	Blue Alkyd/Acryl Paint (RAL 5007)
overall height:	40.2 mm
pilot diameter:	105 mm
bore type:	Round
bolt size:	16 mm
mounting type:	Four-Bolt Piloted
maximum rpm:	4300 rpm
housing material:	Cast Iron
lubrication type:	Lubrication Fitting
locking device:	Set Screw
series:	FYC
expansion type:	Non-Expansion Bearing (Fixed)
manufacturer product page:	Click here
bearing material:	Steel

manufacturer upc number:	7316570516449
radial dynamic load capacity:	33.2 kN
Housing material	Cast iron
A	37.5 mm
B4	8 mm
Db	106.1 mm
RG	1/4-28 UNF
R1	21 mm
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
Basic dynamic load rating C	33.2 kN
Basic static load rating C0	21.6 kN
Fatigue load limit Pu	0.915 kN
Limiting speed with shaft tolerance h6	4300 r/min
Mass unit	2.55 kg
Thread grub screw G2	M8x1
Hexagonal key size for grub screw N	4 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	14 mm
Recommended diameter for attachment bolts, inch G	0.5625 in
Bearing	YAR 209-2F
Housing	FYC 509