

NACHI NU 206 cylindrical roller bearings

Advance NACHI NU 206 cylindrical roller bearings is your source 220 Outer Diameter (mm) for 300x220x60 Size (mm) quality and 300 Bore Diameter (mm) accessories. shop online for home delivery or pick up in one of our 10000 .

Size (mm)	300x220x60
Bore Diameter (mm)	300
Outer Diameter (mm)	220
Width (mm)	60
d	220 mm
D	300 mm
B	60 mm
d2	241 mm
D1	278 mm
b	8.3 mm
K	4.5 mm
r1,2 – min.	2.1 mm
da – min.	231 mm
Da – max.	289 mm
ra – max.	2 mm
Basic dynamic load rating – C	661 kN
Basic static load rating – C0	1080 kN
Fatigue load limit – Pu	93 kN
Reference speed	2000 r/min
Limiting speed	2200 r/min
Calculation factor – e	0.16

Calculation factor – Y1	4.2
Calculation factor – Y2	6.3
Calculation factor – Y0	4
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	14.263
EAN	7316577004741
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch – Metric	Metric
Long Description	220MM Straight Bore; 300MM Outside Diameter; 60MM Width; C0-Medium Clearance; Shaft Mount; Double Ro
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	27.273
Bore	8.661 Inch 220 Millimeter

Outside Diameter	11.811 Inch 300 Millimeter
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Width	2.362 Inch 60 Millimeter
bore diameter:	220 mm
maximum rpm:	2200 RPM
outside diameter:	300 mm
operating temperature range:	Maximum of +390 °F
overall width:	60 mm
cage material:	Steel
bore type:	Straight
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	60 mm
dynamic load capacity:	630 kN
fillet radius:	2 mm
static load capacity:	1080 kN
series:	239
d2 ≈	241 mm
D1 ≈	278 mm
r1,2 min.	2.1 mm
da min.	231 mm
Da max.	289 mm

ra max.	2 mm
Basic dynamic load rating C	661 kN
Basic static load rating C0	1080 kN
Fatigue load limit Pu	93 kN
Calculation factor e	0.16
Calculation factor Y1	4.2
Calculation factor Y2	6.3
Calculation factor Y0	4
Mass bearing	12.5 kg