

NACHI NUP 1013 cylindrical roller bearings

Question NACHI NUP 1013 cylindrical roller bearings ? Find what you need faster 100 mm da 114.3 mm db by entering your information .

da	100 mm
db	114.3 mm
dc	96.838 mm
Da	215.001 mm
Ca	82.804 mm
A1	120.65 mm
A2	187.325 mm
ba	45.244 mm
H	258.762 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	79.375 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	55.563 mm
Housing	SAF 320

Bearing	1320
Lock nut	AN 20
Lock washer	W 20
Stabilizing ring	2 x SR-1620
Labyrinth ring (db shaft position)	LOR 118
PosiTrac Plus contact element (db shaft position)	B10724-117
Labyrinth ring (dc shaft position)	LOR 106
PosiTrac Plus contact element (dc shaft position)	B10724-106
End plug (suffix Y)	EPR 12
Max. speed for PosiTrac Plus seal	1300 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	52.5 kN
Mass pillow block	44.5 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	765.45 g