

NACHI NUP 322 E cylindrical roller bearings

NACHI NUP 322 E cylindrical roller bearings, Units and Housings CAD models , Manufacturing Service . 30x72x19 Size (mm) Get 72 Outer Diameter (mm) Your Free.

Size (mm)	30x72x19
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Width (mm)	19
d	30 mm
D	72 mm
B	19 mm
C	19 mm
r1 min.	1.1 mm
da min.	36.5 mm
Da max.	65.5 mm
ra max.	1.0 mm
Weight	0.387 Kg
Basic dynamic load rating (C)	21,3 kN
Basic static load rating (C0)	6,3 kN
(Grease) Lubrication Speed	9000 r/min
(Oil) Lubrication Speed	11000 r/min
Calculation factor (e)	0.26
Calculation factor (Y0)	2.52
Calculation factor (Y1)	2.40
Inventory	0.0
Manufacturer Name	NACHI

Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-306X
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 3 Deg 1:12 Taper
Long Description	30MM Bore; Tapered Adapter Mount; 72MM Outside Diameter; 19MM Inner Race Width; 19MM Outer Race Width
Inch – Metric	Metric
UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning
Weight / LBS	0.85319
Inner Race Width	0.748 Inch 19 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
Outer Race Width	0.748 Inch 19 Millimeter
Bore	1.181 Inch 30 Millimeter