

NACHI NUP 417 cylindrical roller bearings

are a 95 mm d few brands you will find 145 mm D in our inventory. Find NACHI NUP 417 cylindrical roller bearings to see what's in stock!

d	95 mm
D	145 mm
B	24 mm
rs min	1.5 mm
Radial clearance class	C4
Mass	1.08 kg
Dynamic load, C	60.5 kN
Static load, C ₀	54 kN
Fatigue limit load, C _u	2.24 kN
f ₀	15.8
N _{lim} (oil)	5,300 rpm
N _{lim} (grease)	4,500 rpm
Min operating temperature, T _{min}	-60 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.83 Hz
Characteristic outer ring frequency, BPF ₀	6.56 Hz
Characteristic inner ring frequency, BPF _I	8.44 Hz
da min	103 mm
Da max	137 mm
ra max	1.5 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.08
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	95MM Bore; 145MM Outside Diameter; 24MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6019C4
Weight / LBS	2.67
Outer Race Width	0.945 Inch 24 Millimeter
Bore	3.74 Inch 95 Millimeter
Outside Diameter	5.709 Inch 145 Millimeter