

# NACHI UCTU212+WU500 bearing units

NACHI UCTU212+WU500 bearing units Industries and Applications ? 30 Outer Diameter (mm) We sell discount online as 22x30x16 Size (mm) well as cheap machinery parts.

Size (mm)	22x30x16
Bore Diameter (mm)	22
Outer Diameter (mm)	30
Width (mm)	16
Fw	22 mm
D	30 mm
C	16 mm
rmin	0,3 mm
m	30 g / Weight
Cr	15800 N / Dynamic load rating (radial)
C0r	19900 N / Static load rating (radial)
Cur	3650 N / Fatigue limit load, radial
nG	20000 1/min / Limiting speed
nB	10900 1/min / Reference speed
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.03
EAN	4047643136242
Product Group	B04144

Rolling Element	Needle Roller Bearing
Component	Roller Assembly with Outer Ring – No Inner Ring
Enclosure	Open
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	No
Inch – Metric	Metric
Relubricatable	Yes
Thrust Bearing	No
Long Description	22MM Bore; 30MM Outside Diameter; 16MM Width; Needle Roller Bearing; Roller Assembly with Outer Ring
Other Features	2 Rib Outer Ring   Radial Precision   Steel Cage   Ground Raceway with Rib   Oil Hole
UNSPSC	31171512
Harmonized Tariff Code	8482.99.65.30
Noun	Roller Assembly with Outer Ring
Keyword String	Bearing Needle
Manufacturer Item Number	NK22/16
Weight / LBS	0.066
Bore	0.866 Inch   22 Millimeter
Outside Diameter	1.181 Inch   30 Millimeter
Width	0.63 Inch   16 Millimeter