

NBS AXK 6085 needle roller bearings

Welcome to the NBS AXK 6085 needle roller bearings 250x150x80 Size (mm) 150 Outer Diameter (mm) online seller.

Size (mm)	250x150x80
Bore Diameter (mm)	250
Outer Diameter (mm)	150
Width (mm)	80
d	150 mm
D	250 mm
H	80 mm
d1	245 mm
D1	154 mm
r1,2 – min.	2.1 mm
da – min.	209 mm
Da – max.	191 mm
ra – max.	2 mm
Basic dynamic load rating – C	390 kN
Basic static load rating – C0	1290 kN
Fatigue load limit – Pu	34 kN
Reference speed	900 r/min
Limiting speed	1300 r/min
Minimum load factor – A	10
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	16.305

EAN	7316577121226
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Brass
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row Roller Guided
Long Description	150MM Bore 1; 154MM Bore 2; 250MM Outside Diameter; 80MM Height; Ball Bearing; Single Direction; Not
Inch – Metric	Metric
UNSPSC	31171507
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	51330 M
Weight / LBS	35.913
Bore 1	5.906 Inch 150 Millimeter
Outside Diameter	9.843 Inch 250 Millimeter
Height	3.15 Inch 80 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 2	6.063 Inch 154 Millimeter
d1 ≈	245 mm
D1 ≈	154 mm

r _{1,2} min.	2.1 mm
d _a min.	209 mm
D _a max.	191 mm
r _a max.	2 mm
Basic dynamic load rating C	423 kN
Basic static load rating C ₀	1460 kN
Fatigue load limit P _u	39 kN
Minimum load factor A	10
Mass bearing (including seat washer where applicable)	16.5 kg