

# NBS HK 4516 needle roller bearings

We Provide Extensive NBS HK 4516 needle roller bearings Selection And Competitive 30x62x25 Size (mm) Wholesale Pricing. 62 Outer Diameter (mm)

Size (mm)	30x62x25
Bore Diameter (mm)	30
Outer Diameter (mm)	62
Width (mm)	25
d	30 mm
D	62 mm
T	25 mm
B	25 mm
C	19,5 mm
a	16,3 mm
r min.	1 mm
r2 min.	1 mm
da min.	35,5 mm
da max	36 mm
Da min	53 mm
Da max.	56,5 mm
Db min.	59 mm
ra max.	1 mm
rb max.	1 mm
Weight	0,359 Kg
Basic dynamic load rating (C)	66,4 kN
Basic static load rating (C0)	79,4 kN

(Grease) Lubrication Speed	6500 r/min
(Oil) Lubrication Speed	8700 r/min
Calculation factor (e)	0,34
Calculation factor (Y0)	0,97
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.36
EAN	0605790123870
Product Group	B04334
Precision Class	Standard
Component	Assembly
Basic Number	33206
Number of Tapered Rows	Single Row
Inch – Metric	Metric
Other Features	High Load Capacity
Long Description	Assembly; Standard Precision; 30MM Bore; 62MM Outside Diameter; 25MM Assembly Width; Single Row of R
UNSPSC	31171516
Harmonized Tariff Code	8482.20.00.00
Noun	Bearing
Keyword String	Tapered
Manufacturer Item Number	33206JR
Weight / LBS	0.791
Flange Outside Diameter	0 Inch   0 Millimeter
Outside Diameter	2.441 Inch   62 Millimeter
Bore	1.181 Inch   30 Millimeter
Assembly Width	0.984 Inch   25 Millimeter

Bearing No.	33206JR
r(min)	1
r1(min)	1
Cr	83.1
C0r	79.4
Cu	11.6
Grease lub.	6500
Oil lub.	8700
a(mm)	16.3
da(min)	35.5
db(max)	36
Da(max)	56.5
Da(min)	53
Db(min)	59
Sa(min)	5
Sb(min)	5.5
ra(max)	1
rb(max)	1
e	0.34
Y1	1.76
Y0	0.97
(Refer.) Mass (kg)	0.359