

# NBS K 14x18x10 needle roller bearings

Request A Quote For Your 0.0 Inventory Special NBS K 14x18x10 needle roller bearings Needs Today! Free Quotes. ISO 9001 REXNORD Manufacturer Name certified.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.41  |
| EAN                       | 0793699384932   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 4 Bolt Flange Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | High Test Iron  |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | WG231EL   |
| Seals                     | Single Lip Contact  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Flange Block; 1-15/16" Bore; 4.9" Bolt Circle; 3-1/2" Bolt Spacing; 1 Piece So |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Intermediate Duty   Extended Inner Race   Inboard Mount |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | FRWG231E   |
| Manufacturer Internal Number       | 0138493  |
| Weight / LBS                       | 3.1  |
| Nominal Bolt Circle Diameter Round | 4.9 Inch   125.7 Millimeter  |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter  |
| D                                  | 1.719 Inch   43.663 Millimeter   |
| Bolt Spacing                       | 3.5 Inch   88.9 Millimeter   |
| d                                  | 1.938 Inch   49.225 Millimeter   |