

# NBS K 50x57x18 needle roller bearings

Manufacturers 80.963 mm dc of all are represented in 85 mm da our partial list of clients. Contact Gary for a complete NBS K 50x57x18 needle roller bearings list of clients and projects.

da	85 mm
db	100.013 mm
dc	80.963 mm
Da	150 mm
Ca	45.796 mm
A1	88.9 mm
A2	127 mm
S	4.763 mm
ba	35.719 mm
H	182.166 mm
H1	95.25 mm
H2	31.75 mm
J min.	250.825 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT
h	34.925 mm

Housing	FSAF 217
Bearing	22217 E
Lock nut	AN 17
Lock washer	W 17
Stabilizing ring	SR-17-14
Labyrinth ring (db shaft position)	LOR 89
PosiTrac Plus contact element (db shaft position)	B10724-89
Labyrinth ring (dc shaft position)	LOR 63
PosiTrac Plus contact element (dc shaft position)	B10724-64
End plug (suffix Y)	EPR 9
Max. speed for PosiTrac Plus seal	1450 r/min
P60°	61.4 kN
P90°	36.9 kN
P120°	23.1 kN
P150°	20.9 kN
P180°	25.4 kN
Pa	16.5 kN
Mass pillow block	15.9 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	110.56 g