

NBS NA 6910 ZW needle roller bearings

Various types 50.8×65.088×25.4 Size (mm) and sizes to accommodate 65,088 Outer Diameter (mm) your NBS NA 6910 ZW needle roller bearings requirements.

Size (mm)	50.8×65.088×25.4
Bore Diameter (mm)	50,8
Outer Diameter (mm)	65,088
Width (mm)	25,4
Fw	50,8 mm
D	65,088 mm
C	25,4 mm
r5 min.	1,52 mm
Weight	0,2 Kg
Basic dynamic load rating (C)	53,8 kN
Basic static load rating (C0)	93 kN
(Grease) Lubrication Speed	8600 r/min
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.2
EAN	0605790190728
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly with Outer Ring – No Inner Ring
Enclosure	Open

Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	No
Inch – Metric	Inch
Relubricatable	Yes
Thrust Bearing	No
Long Description	2" Bore; 2-9/16" Outside Diameter; 1" Width; Needle Roller Bearing; Roller Assembly w
Other Features	2 Rib Outer Ring Steel Cage Heavy Duty Oil Hole
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer Item Number	HJ-324116
Weight / LBS	0.44
Outside Diameter	2.563 Inch 65.1 Millimeter
Width	1 Inch 25.4 Millimeter
Bore	2 Inch 50.8 Millimeter
Bearing No.	HJ-324116
rs(min)	1.52
Used with inner ring No.	IR-273216
Cr	25.4
C0r	93.0
Cu	14.7
Grease lub.	5600

Oil lub.	8600
(Refer.)Mass(kg)	0.200
Clearance fit S(h6)(max.)	50.800
Clearance fit S(h6)(min.)	50.782
Clearance fit H(H7)(max.)	65.118
Clearance fit H(H7)(min.)	65.088
Tight transition fit S(f6)(max.)	50.770
Tight transition fit S(f6)(min.)	50.752
Tight transition fit H(N7)(max.)	65.080
Tight transition fit H(N7)(min.)	65.049
Da	60.33