

NBS NAO 50x68x20 needle roller bearings

NBS NAO 50x68x20 needle roller bearings Product Brochures , Manufacturing Service . Get Your 0.0 Inventory Free.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	6.13
EAN	7316576664670
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22213
Seals	Garter Spring
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch – Metric	Inch
Long Description	4 Bolt Round Flange Cartridge; 2-1/2" Bore; 6-1/2" Bolt Circle; 4.6" Bolt Spacing; 1

Other Features	Double Row Heavy Duty Open End With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FYRP 2.1/2-3
Weight / LBS	13.5
Nominal Bolt Circle Diameter Round	6.5 Inch 165 Millimeter
d	2.5 Inch 63.5 Millimeter
Cartridge Pilot Diameter	5.5 Inch 139.7 Millimeter
D	3.375 Inch 85.725 Millimeter
Bolt Spacing	4.6 Inch 117 Millimeter
Cartridge Pilot Depth	1 Inch 25.4 Millimeter
bore diameter:	2-1/2 in
expansion type:	Non-Expansion Bearing (Fixed)
bolt center-to-center length:	6.5000 in
seal type:	Radial Shaft Seal
overall length/diameter:	7.6250 in
overall depth:	3-1/2 in
flange mounting type:	Four-Bolt Piloted Flange
radial dynamic load capacity:	33300 lb
bearing type:	Spherical Roller
radial static load capacity:	41100 lb
housing construction:	Solid Flange Mount
operating temperature range:	-5 to +230 °F
bore type:	Round

maximum rpm:	1100 RPM
duty type:	Standard Duty
finish/coating:	Uncoated
housing material:	Cast Iron
lubrication type:	Lubrication Fitting
locking device:	Set Screw
series:	222