

NBS SL024838 cylindrical roller bearings

What N/A Minimum Buy Quantity are the types of NBS SL024838 cylindrical roller bearings ? Manufacturing Service . Get Your Free, 0.0 Inventory Instant price, design review.

| | |
|----------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 140.13 |
| EAN | 7316576620942 |
| Product Group | B04311 |
| Rolling Element | Spherical Roller Bearing |
| Self Aligning | Yes |
| Component Description | Roller Assembly plus Raceways |
| Thrust Bearing | Yes |
| Single or Double Direction | Single Direction |
| Banded | No |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Other Features | Single Row Window Type Cage |
| Long Description | 300MM Bore 1; 392MM Bore 2; 540MM Outside Diameter; 145MM Height; Spherical Roller Bearing; Single D |
| Inch – Metric | Metric |
| UNSPSC | 31171507 |
| Harmonized Tariff Code | 8482.30.00.40 |
| Noun | Bearing |

| | |
|-------------------------------------|------------------------------|
| Keyword 3 | Spherical |
| Keyword String | Thrust Roller Spherical |
| Manufacturer Item Number | 29460 E |
| Weight / LBS | 308.647 |
| D | 540 mm |
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |
| Bore 1 | 11.811 Inch 300 Millimeter |
| Height | 5.709 Inch 145 Millimeter |
| Bore 2 | 15.433 Inch 392 Millimeter |
| bore diameter: | 300 mm |
| dynamic load capacity: | 5000 kN |
| outside diameter: | 540 mm |
| maximum rpm: | 1200 RPM |
| overall width: | 145 mm |
| separable type: | Non-Separable |
| cage material: | Steel |
| fillet radius: | 5 mm |
| static load capacity: | 16600 kN |
| series: | 294 |
| d | 300 mm |
| H | 145 mm |
| d1 ≈ | 485 mm |
| D1 ≈ | 392 mm |
| B | 95 mm |
| B1 | 130.3 mm |
| C | 70.5 mm |
| s | 175 mm |
| r1,2 min. | 6 mm |

| | |
|-----------------------------|------------|
| da min. | 415 mm |
| db1 max. | 319 mm |
| db2 max. | 340 mm |
| Da max. | 465 mm |
| ra max. | 5 mm |
| Basic dynamic load rating C | 5000 kN |
| Basic static load rating C0 | 16600 kN |
| Fatigue load limit Pu | 1340 kN |
| Reference speed | 670 r/min |
| Limiting speed | 1200 r/min |
| Minimum axial load factor A | 24 |
| Mass bearing | 140 kg |