

NKE 22248-K-MB-W33+AH3148 spherical roller bearings

Question NKE 22248-K-MB-W33+AH3148 spherical roller bearings 120 mm D ? Find what you need 55 mm d faster by entering your information .

d	55 mm
D	120 mm
B	29 mm
E	106.5 mm
F	70.5 mm
d1	77.7 mm
rs min	2 mm
r1s min	2 mm
Radial clearance class	C4
Mass (without HJ ring)	1.45 kg
Dynamic load, C	137 kN
Static load, C0	143 kN
Fatigue limit load, Cu	17.4 kN
Nlim (oil)	6,300 rpm
Nlim (grease)	5,300 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.71 Hz
Characteristic outer ring frequency, BPF0	5.18 Hz

Characteristic inner ring frequency, BPI	7.82 Hz
da min	64 mm
da max	69 mm
dc min	80 mm
Da max	111 mm
ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.42
EAN	4547359123173
Product Group	B04144
Bore Profile	Straight
Cage Material	Nylon
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C4-Extra Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID

Long Description	55MM Bore; Straight Bore Profile; 120MM Outside Diameter; 29MM Width; Nylon Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NJ311ET2XC4
Weight / LBS	3.13
Bore	2.165 Inch 55 Millimeter
Width	1.142 Inch 29 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter