

NKE 52232-MP thrust ball bearings

The online NKE 52232-MP thrust ball bearings parts store gives you immediate access to a selection of more 8 mm d than 1.4 million new, used, remanufactured.

| | |
|---------------------------------|------------|
| d | 8 mm |
| D | 22 mm |
| B | 7 mm |
| rs min | 0.3 mm |
| Radial clearance class | CN |
| Mass | 0.01 kg |
| Dynamic load, C | 3.35 kN |
| Static load, C0 | 1.4 kN |
| Fatigue limit load, Cu | 0.06 kN |
| f0 | 12.5 |
| Nlim (oil) | 27,000 rpm |
| Nlim (grease) | 23,000 rpm |
| Min operating temperature, Tmin | -30 °C |
| Max operating temperature, Tmax | 120 °C |
| da min | 10 mm |
| da max | 12.2 mm |
| Da max | 20 mm |
| ra max | 0.3 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |

| | |
|---------------------------------|--|
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.012 |
| Product Group | B00308 |
| Enclosure | 1 Seal |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 8MM Bore; 22MM Outside Diameter; 7MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No Fil |
| Other Features | Deep Groove Low Torque Fluorinated Elastomer Rubber Friction Seal -30 To 230 Deg C |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 0.02645 |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 0.276 Inch 7 Millimeter |
| Bore | 0.315 Inch 8 Millimeter |

| | |
|------------------|----------------------------|
| Outside Diameter | 0.866 Inch 22 Millimeter |
|------------------|----------------------------|