

# NKE 53202+U202 thrust ball bearings

are a few brands you 30x62x19.8 Size (mm) will find in our inventory. Find NKE 53202+U202 thrust ball bearings to see what's in stock!

Size (mm)	30x62x19.8
Bore Diameter (mm)	30
Outer Diameter (mm)	62
Width (mm)	19,8
D	62 mm
d	30 mm
C	19.8 mm
B	20 mm
D1	43 mm
F	35 mm
r1,2 – min.	1 mm
r3,4 – min.	0.3 mm
Basic dynamic load rating – C	17.9 kN
Basic static load rating – C0	25.5 kN
Fatigue load limit – Pu	3 kN
Maximum dynamic radial loads – Fr	28.5 kN
Maximum static radial loads – F0r	40.5 kN
Limiting speed	2800 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.32

EAN	7316577113610
Product Group	B04144
Roller Surface Profile	Crowned
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Needle Bearing
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Caged   With Inner Ring   Lip Seal
Long Description	30MM Bore; 62MM Roller Diameter; 19.8MM Roller Width; Crowned Roller; Yoke Type; Sealed; Needle Bear
UNSPSC	31171530
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	NA 2206.2RS
Weight / LBS	0.705
Roller Width	0.78 Inch   19.8 Millimeter
Roller Diameter	2.441 Inch   62 Millimeter
Bore	1.181 Inch   30 Millimeter
roller diameter:	62 mm
radial static load capacity:	40.5 kN
roller width:	19.8 mm
roller material:	Chrome Steel

bore diameter:	30 mm
maximum rpm:	2600 RPM
roller shape:	Crowned
lubrication hole location:	Inner Ring
bearing element:	Needle Rollers
axial dynamic load capacity:	17.6 kN
closure type:	Sealed
axial static load capacity:	24.5 kN
operating temperature range:	Maximum of +280 °F
finish/coating:	Uncoated
radial dynamic load capacity:	28.5 kN
standards met:	ANSI/ABMA Standard 18.1
r1,2 min.	1 mm
r3,4 min.	0.3 mm
Basic dynamic load rating C	17.9 kN
Basic static load rating C0	25.5 kN
Fatigue load limit Pu	3.05 kN
Maximum dynamic radial load Fr max.	28.5 kN
Maximum static radial load F0r max.	40.5 kN
Mass support roller	0.32 kg