

NKE 53318+U318 thrust ball bearings

NKE 53318+U318 thrust ball bearings Product N/A Minimum Buy Quantity Brochures NSK Manufacturer Name , 0.0 Inventory Manufacturing Service . Get Your Free.

Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight	0.15
EAN	0029176073007
Product Group	B00152
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	25 Degree
Internal Clearance	C3-Loose
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	25MM Bore; 52MM Outside Diameter; 20.6MM Width; Open; No Flush Ground; Ball Bearing; Double Row of B
UNSPSC	31171531

Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	5205TNC3
Weight / LBS	0.331
d	0.984 Inch 25 Millimeter
B	0.811 Inch 20.6 Millimeter
D	2.047 Inch 52 Millimeter
bore diameter:	25 mm
operating temperature range:	Maximum of +250 °F
outside diameter:	52 mm
cage material:	Synthetic Resin
overall width:	0.8125 in
outer ring width:	20.6 mm
contact angle:	25 °
maximum rpm:	11000 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C3
precision rating:	ABEC 1 (ISO Class Normal)
closure type:	Open
fillet radius:	1 mm
radial dynamic load capacity:	2170 kgf
series:	52
radial static load capacity:	1500 kgf