

NKE 53426-MP+U426 thrust ball bearings

How 30 mm d do you find the NKE 53426-MP+U426 thrust ball bearings specification? Manufacturers Online Free check

d	30 mm
D	62 mm
B	16 mm
C	14 mm
T	17.25 mm
d1	45 mm
a	13.5 mm
rs min	1 mm
r1s min	1 mm
e	0.37
Y2	1.6
Y0	0.88
Mass	0.24 kg
ISO 355 reference	T3DB030
Dynamic load, C	43.5 kN
Rating life coefficient, A2	1.9
Static load, C0	48 kN
Fatigue limit load, Cu	5.9 kN
Nlim (oil)	8,400 rpm
Nlim (grease)	6,300 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz

Characteristic rolling element frequency, BSF	5.82 Hz
Characteristic outer ring frequency, BPF0	7.12 Hz
Characteristic inner ring frequency, BRFI	9.88 Hz
da max	37 mm
db min	35.5 mm
Da min	53 mm
Da max	56.5 mm
Db min	57 mm
Ca min	2 mm
Cb min	3 mm
ra max	1 mm
r1a max	1 mm