

# NKE 61980-MA deep groove ball bearings

NKE 61980-MA deep groove ball bearings Needs Analysis N/A  
Minimum Buy Quantity , Manufacturing 0.0 Inventory TIMKEN  
Manufacturer Name Service . Get Your Free.

|                           |                                    |
|---------------------------|------------------------------------|
| Inventory                 | 0.0                                |
| Manufacturer Name         | TIMKEN                             |
| Minimum Buy Quantity      | N/A                                |
| Weight                    | 24.97                              |
| EAN                       | 0883450181945                      |
| Product Group             | M06288                             |
| Number of Mounting Holes  | 2                                  |
| Mounting Method           | V Lock                             |
| Housing Style             | 2 Bolt Pillow Block                |
| Rolling Element           | Spherical Roller Bearing           |
| Housing Material          | Cast Steel                         |
| Expansion / Non-expansion | Expansion                          |
| Mounting Bolts            | 7/8 Inch                           |
| Relubricatable            | Yes                                |
| Insert Part Number        | 22220                              |
| Seals                     | Teflon Labyrinth                   |
| Housing Configuration     | 1 Piece Solid                      |
| Inch – Metric             | Inch                               |
| Other Features            | Double Row   Double Nut   SN Style |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 3-1/4" Bore; 4.409" Base to Center Height; V Lock Mount; Spherical Ro |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Weight / LBS                  | 65   |
| D                             | 4.63 Inch   117.602 Millimeter   |
| d                             | 3.25 Inch   82.55 Millimeter   |
| Bolt Spacing Maximum          | 12.875 Inch   327.025Millimeter  |
| Nominal Bolt Center to Center | 11.9 Inch   302.3 Millimeter   |
| B                             | 4.409 Inch   112 Millimeter  |
| Bolt Spacing Minimum          | 10.875 Inch   276.225Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |